

Uphire

Equipment Specialists


1300 87 44 73

www.uphire.com.au

PRODUCT RANGE



Scissor Lifts



Forklifts



Boom Lifts



Telehandlers



Knuckle Boom Lifts



Scaffold



Spider Lifts



Lighting Towers



Vertical Lifts



Portable Equipment

EWP Operator Licence Training



www.uphire.com.au

BOOM LIFTS

Make /Model	Platform Height	Horizontal Outreach	Platform Capacity	Overall Width	Weight (kg)	Platform Size
Genie S45	13.72m	11.18m	227kg	2.3m	7 151kg	0.91 x 2.44m
JLG 460SJ	14.02m	12.34m	230kg	2.3m	7 930kg	0.91 x 2.44m
Genie S65	19.8m	17.10m	227kg	2.49m	10 349kg	0.91 x 2.44m
JLG 660SJ	20.31m	17.30m	230kg	2.42m	13 550kg	0.91 x 2.44m
Genie S85	25.90m	23.30m	227kg	2.49m	16 992kg	0.91 x 2.44m
JLG 860SJ	26.21m	22.86m	230kg	2.49m	18 500kg	0.91 x 2.44m
Genie S125	38.15m	24.38m	227kg	2.49m	20 739kg	0.91 x 2.44m
JLG 1350 SJP	41.15m	24.38m	227kg	2.49m	20 411 kg	0.91 x 2.44m
JLG 1500 SJ	45.7m	24.38m	227kg	2.49m	21 773kg	0.91 x 2.44m
Genie SX-180	54.86m	24.38m	340kg	2.49m	24 494 kg	0.91 x 2.44m



Genie S45



JLG 660SJ



Genie S85



SX180

SPIDER LIFTS



For all of your tight access areas when you need a lightweight machine. A range of models are available from 13m to 37m. Due to the specialist nature of projects requiring Spider Lifts, please contact us to determine the best model for your project.

Specifications to be used as a guide only. Variations in weight and size can occur according to year model and special features. Please contact us if you have any further questions regarding specifications

KNUCKLE BOOM LIFTS

ELECTRIC KNUCKLE BOOMS

Make /Model	Platform Height	Horizontal Outreach	Platform Capacity	Overall Width	Weight (kg)	Platform Size
Genie Z30/20N	8.80m	6.3m	227kg	1.20m	6622kg	0.76 x 1.17m
JLG 300AJP	9.14m	6.25m	230kg	1.22m	7200kg	0.76 x 1.22m
Nifty 120T	10.20m	6.10m	200kg	3.55m	1400kg	0.65 x 1.10m
Genie Z34/ 22N	10.52m	6.78m	227kg	1.47m	5216kg	0.76 x 1.42m
JLG 400AJPN	12.19m	6.83m	230kg	1.50m	6760kg	0.76 x 1.22m
Genie Z40/23N RJ	12.32m	6.91m	227kg	1.50m	6940kg	0.76 x 1.17m
JLG E450AJ	13.72m	7.24m	230kg	1.75m	6532kg	0.76 x 1.22m
Genie Z45/25J DC	13.90m	7.65m	227kg	1.70m	7394kg	0.76 x 1.83m
JLG M600JP	18.29m	13.06m	230kg	2.44m	6760kg	0.76 x 1.80m

DIESEL KNUCKLE BOOMS

Make /Model	Platform Height	Horizontal Outreach	Platform Capacity	Overall Width	Weight (kg)	Platform Size
Nifty 120T	10.20m	6.10m	200kg	3.55m	1400kg	0.65 x 1.10m
JLG 340AJ	10.31m	6.07m	227kg	1.93m	4400kg	0.76 x 1.22m
Genie Z34/ 22IC	10.62m	6.78m	227kg	1.85m	4854kg	0.75 x 1.42m
Genie Z40/23N RJ	12.32m	6.91m	227kg	1.17m	6940kg	0.76 x 1.17m
JLG 450AJ	13.72m	7.47m	230kg	2.08m	7430kg	0.76 x 1.83m
Genie Z45/ 25J RT	13.90m	7.65m	227kg	2.29m	6260kg	0.76 x 1.83m
Skyjack SJ46 AJ	14.15m	7.68m	227kg	2.24m	6981kg	0.76 x 1.83m
Nifty HR17	15.20m	9.40m	225kg	2.0m	5000kg	0.85 x 1.80m
Genie Z51/30J RT	15.60m	9.25m	227kg	2.29m	7240kg	0.76 x 1.83m
JLG 510AJ	15.81m	9.48m	230kg	2.34m	7685kg	0.76 x 1.83m
JLG 600AJ	18.29m	12.12m	230kg	2.44m	10025kg	0.91 x 1.83m
Genie Z60/34	18.30m	11.05m	227kg	2.44m	9900kg	0.76 x 1.83m
JLG 800AJ	24.40m	15.8m	230kg	2.44m	15500kg	0.91 x 1.83m
JLG 1250 AJP	38.10m	19.25m	227kg	2.49kg	19960kg	0.91 x 2.44m
Genie ZX135/70	41.15m	21.26m	272kg	2.46m	20260kg	0.91 x 1.83m



Z34RT



JLG E450AJ



JLG 510AJ



Genie ZX135/70

Specifications to be used as a guide only. Variations in weight and size can occur according to year model and special features. Please contact us if you have any further questions regarding specifications

SCISSOR LIFTS

SCISSOR LIFTS ELECTRIC							
Make /Model	Platform Height	Power Source	Working Height (approx)	Platform Capacity	Overall Width	Weight (kg)	Platform Size
Skyjack SJ3215	15ft/4.57m	Electric	6.57m	227kg	0.81m	1120kg	0.66x1.63m
JLG 1930ES	19ft/5.72m	Electric	7.7m	227kg	0.76m	1550kg	0.76 x 1.87m
Genie GS1932	19ft/ 5.8m	Electric	7.8m	227kg	0.81m	1503kg	0.74 x 1.64m
Haulotte Optimum 8	19ft/ 5.77m	Electric	7.77m	230kg	0.79m	1520kg	1.72 x 0.74m
JLG R6	19ft/5.64m	Electric	7.64m	230kg	0.81m	1588kg	0.75 x 1.88m
JLG 2030ES	20ft/6m	Electric	8.1m	360kg	0.76m	2065kg	0.76 x 2.3m
Genie GS2046	20ft/6m	Electric	8.1m	544kg	1.17m	1973kg	1.15 x 2.26m
JLG 2630ES	26ft/ 7.8m	Electric	9.75m	230kg	0.76m	2200kg	0.76 x 2.3m
JLG 2646ES (GS2646)	26ft/7.92m	Electric	9.92m	450kg	1.17m	2600kg	1.12 x 2.5m
Genie GS3232 (Narrow)	32ft/ 9.75m	Electric	11.75m	227kg	0.81m	2352kg	0.81 x 2.26m
Genie GS3246	32ft/9.75m	Electric	11.75m	318kg	1.16m	2812kg	1.16 x 2.26m
GS4047	38ft/11.7m	Electric	13.7m	350kg	1.16m	3222kg	1.16 x 2.26m
JLG 4069LE	40ft/12m	BIO	14.19m	360kg	1.75m	5300kg	1.65 x 2.92m
TRACK SCISSOR LIFTS – PETROL/ ELECTRIC							
Athena 850	19ft/5.9m	Hybrid	7.9m	250kg	1.3m	1990kg	0.71 x 1.47m
SCISSOR LIFTS DIESEL							
Genie GS2668RT	26ft/7.92m	4X4 Diesel	9.92m	567kg	1.73m	3415kg	1.55 x 2.51m
Skyjack SJ6826RT	26ft / 7.92m	4x4 Diesel	9.92m	454kg	1.72m	3305kg	1.42 x 2.44m
Genie GS3268RT	32ft/9.75m	4X4 Diesel	11.75m	454kg	1.73m	4153kg	1.55 x 2.51m
Skyjack SJ6832RT	32ft/ 9.75m	4x4 Diesel	11.75m	454kg	1.72m	3655kg	1.42 x 2.44m
Genie GS4390RT	43ft/13m	4X4 Diesel	15.11m	680kg	2.29m	7692kg	1.83 x 5.34m
Skyjack SJ 9250	50ft/15.24m	4X4 Diesel	17.24m	681kg	2.34m	7407kg	1.88 x 4.27m
Genie GS5390RT	53ft/ 16.15m	4x4 Diesel	18.15m	680kg	2.29m	8274kg	1.83 x 5.34m

VERTICAL LIFTS

Make /Model	Platform Height	Platform Capacity	Overall Width	Overall Length	Weight
JLG 1230ES	3.66m	227kg	0.76m	1.36m	790kg
Genie GRC12	3.66m	227kg	0.80m	1.37m	948kg
Genie GR15	4.47m	227kg	0.75m	1.35m	975kg
Genie GR20	6.07m	159kg	0.80m	1.35m	1 112kg
Haulotte Star 10	8.00m	200kg	1.00m	2.65m	2 760kg
JLG Toucan 10E	8.10m	200kg	0.99m	2.82m	2 990kg
Genie AWP30	9.00m	159kg	0.74m	1.35m	393kg

Specifications to be used as a guide only. Variations in weight and size can occur according to year model and special features. Please contact us if you have any further questions regarding specifications

FORKLIFTS

Manufacturer	Capacity	Mast Height	Fuel Type	Container Mast
Manitou	2.5T	4M	Diesel	
Nissan	2.5T	4.3M	Dual Fuel	Yes
Nissan	2.5T	4.7M	Dual Fuel	Yes
Nissan	2.5T	6M	Dual Fuel	No
Toyota	2.5T	4.5M	Dual Fuel	Yes
Toyota	2.5T	6M	Gas	No
Nissan	3T	6M	Dual Fuel	No



Toyota 2.5T Forklift



Nissan 2.5T Dual Fuel Forklift

TELEHANDLERS

Make /Model	Max Lift Height	Max Forward Reach	Rated Max Load	Weight
Merlo 25.6	5.9m	3.3m	2500kg	4750kg
Merlo 28.8	8.2m	5.3m	2800kg	6040kg
Genie GTH-3007	6.9m	3.9m	3000kg	6100kg
Merlo 30.8	7.7m	5.4m	3000kg	6150kg
Dieci 35.10	9.75m	6.5m	3500kg	7700kg
Merlo 38.13	12.6m	8.6m	3800kg	8650kg
Dieci 40.17	16.9m	12.7m	4000kg	12100kg
Merlo 60.10	9.55m	5.5m	6000kg	9890kg



Merlo 25.6



Dieci 35.10

Specifications to be used as a guide only. Variations in weight and size can occur according to year model and special features. Please contact us if you have any further questions regarding specifications

HYBRID LIGHTING TOWERS

The LLTT-H is a true hybrid lighting tower which is market leading in fuel efficiency, labour costs, reduced emissions and noise, as well as being positioned on fully galvanised trailers.

SPECIFICATIONS	
Engine	350W Hybrid Engine/ Battery/ Solar/ AC Kubota Z482-EB
Fuel Type	Diesel
Fuel Consumption	1.6L Per Day (when engine runs)
Running Time (Hours)	200+ Hrs/ 10hrs Indefinite using solar power
Fuel Tank Capacity	120L



SCAFFOLD

UPHIRE has several models of aluminium Scaffolding available. Our scaffolding range includes light weight and easy to manoeuvre options for interior projects as well as heavy duty adjustable scaffolds for large, outdoor, construction projects.

These stable work platforms come in handy for all kinds of work including building maintenance and cleaning to heavy duty construction. Painters, bricklayers, tilers, roofers and electricians will love the generous platform space that can hold all of the tools and supplies in addition to your crew so that you can get your project completed.

For full scaffold specs and a quote call **1300 87 44 73** or visit www.uphire.com.au

PORTABLE EQUIPMENT

Uphire offers a range of portable equipment to complete your project needs, including towable trailer mounted booms, water trailers, generators and push around personnel lifts.



Specifications to be used as a guide only. Variations in weight and size can occur according to year model and special features. Please contact us if you have any further questions regarding specifications

TRAINING

Uphire is an accredited provider of the EWP Operator Licence (Yellow Card) and we run regular courses at our head office. We are also able to organise Telehandler Gold Card Training for you or your team. For full course details and a quote call 1300 87 44 73 or visit www.uphire.com.au

NOTES

THE UPHIRE DIFFERENCE

SITE INSPECTION

Uphire can provide a free site inspection to assist you to select the right piece of equipment for your job. A site inspection can save time and money by ensuring the equipment is the most suitable for the task and location.

PRICING POLICY

Uphire supplies sales, hire, service and transport of new equipment from the world's leading manufacturers.

Unlike other hire companies, Uphire does not charge:

- PPSR Registration fees
- Environmental Levy
- Administration Fees

WORKPLACE HEALTH AND SAFETY

Comprehensive, CM3 prequalified WHS management system. Including:

- Processes for reporting and correction of incidents, hazards and non-conformances
- Processes for monitoring and analysing WHS performance
- Safety data sheets for hazardous substances
- Safe work method statements for high risk work processes
- Licenses, qualifications and competencies register for all employees
- Induction program
- Processes for the management and monitoring of subcontractors
- Emergency procedures

AWARDS & RECOGNITION



UPHIRE IS A MEMBER OF:

